

# 82710SC1

10' DuraTech® Web SRL with Steel Snap Hook, Includes Steel Anchorage Carabiner

**Features :**

- Compact size is simple to install and relocate as worksite changes require
- Dyneema® web lifeline resists abrasion while providing trusted strength.
- Overmolded glass-filled nylon housing contributes unmatched impact resistance
- Internal inertial braking system provides smooth deceleration with minimal fall forces
- Integrated aluminum alloy swivel-eye helps to prevent lifeline twisting for smooth operation
- Features alloy steel snap hook lifeline connector
- Includes alloy steel anchorage carabiner
- Complies with ANSI Z359.14-2014



Material Specifications	
<b>Webbing</b>	Dyneema®/Polyester blend; 4,500 lb min.
<b>Lifeline Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
<b>Anchorage Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
<b>Static Strength</b>	3,000 lb min.
<b>ANSI SRL Class</b>	Class B
<b>Avg. Arrest Force</b>	900 lb
<b>Max. Arrest Force</b>	1,800 lb
<b>Max. Arrest Distance</b>	54"
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 310 lb max.

Compliant With:	
<b>ANSI</b>	Z359.14-2014
<b>OSHA</b>	1926.502 and 1910.66
<b>CSA</b>	Z259.2.2-2017

Sizes & Part Numbers		
82710SC1 (ANSI Compliant)	C82710SC1 (CSA Compliant)	