

Alair® ANSI • CE •

Straight temples // Integrated nosepiece
// Custom imprinting available

Lens and Temples | 7 Variations

- S3210S •• Clear
- S3210ST •• Clear **H2X AF**
- S3220S •• Gray
- S3260S •• Infinity Blue
- S3270S • Silver Mirror
- S3275S • Blue Mirror
- S3280S • I/O Mirror



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
S3210S	P Z87 + U6	P Z87 +	Weight: 22 gm	Lens: polycarbonate
S3210ST	P Z87 + U6	P Z87 +	PD: 68 mm	Temples: polycarbonate
S3220S	P Z87 + U6 L2.5	P Z87 +	Bridge: 12 mm	Hinge: polycarbonate
S3260S	P Z87 + S	P Z87 +	Lens base: 9.5 curve	Screw: stainless steel
S3270S	P Z87 + S	P Z87 +	Lens size diagonal: 73 mm	Nosepiece: polycarbonate
S3275S	P Z87 + S	P Z87 +	Lens size vertical: 42 mm	
S3280S	P Z87 + U6 L1.7	P Z87 +	Lens thickness: 2.45 mm	

Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

General Specifications

Weight: 22 gm

PD: 68 mm

Bridge: 12 mm

Lens base: 9.5 curve

Lens size diagonal: 73 mm

Lens size vertical: 42 mm

Lens thickness: 2.45 mm

Overall length (lens - tip): 158 mm

Overall width (hinge - hinge): 134 mm

Closest point between temple tips: 84 mm

Closest point between lens: 8 mm