









Atoka® ANSI • CSA •



RUBBER TIPS

Integrated nosepiece // Soft non-slip rubber temple tips provide non-binding fit // Custom imprinting available

Lens and Temples | 8 Variations

	S9110S ●●	Clear
	S9110ST ●●	Clear H2X AF
	S9120S ●●	Gray
	S9120ST ●●	Gray H2X AF
	S9130S ●●	Amber
	S9160S ●●	Infinity Blue
	S9180S ●●	I/O Mirror
	S9180ST ●●	I/O Mirror AF



General Specifications

Weight: 22.2 gm
 Bridge: 12.7 mm
 Lens base: 10 curve
 Lens size diagonal: 79 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.5 mm
 Overall length (lens - tip): 157 mm
 Overall width (hinge - hinge): 137mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Temple Tip: polyvinyl chloride (PVC)
 Nosepiece: polycarbonate
 Hinge: polycarbonate

Part No.	Lens Marking	Temple Marking
S9110S	P Z87 + U6	P Z87 + / P c SEI Z94.3
S9110ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
S9120S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
S9120ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
S9130S	P Z87 + S	P Z87 + / P c SEI Z94.3
S9160S	P Z87 + S	P Z87 + / P c SEI Z94.3
S9180S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
S9180ST	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices