





# INSULATED LATEX DIPPED



## GL506C

HPPE + Acrylic | Latex | Sandy + Smooth



ANSI/ISEA 105 – CUT A5 | ABRASION 5 | PUNCTURE 4  
 EN388 – ABRASION 3 | CUT X | TEAR 4 | PUNCTURE 3 | CUT TDM-100 E  
 EN511 –CONVECTIVE COLD X | CONTACT COLD 2 | WATER IMPERMEABILITY X

Double dipped // Sandy latex coating on the palm and fingers provides an effective grip in dry and oily situations // Smooth latex full dipped coating keeps hands dry in wet applications // 13 gauge outer HPPE cut-resistant liner provides comfort and dexterity // 10 gauge inner acrylic liner provides insulation and moisture resistance // Contact cold protection down to as low as -22°F/-30°C // Knit cuff creates a snug fit to keep out debris

### Suggested Applications

Commercial Fishing // Construction // Food Processing // Outdoor Activities // Refrigerated Area // Utilities

### Glove Breakdown

Type: Insulated Dipped Glove
Material: Sandy + Smooth Latex
Outer Liner: 13 Gauge HPPE
Inner Liner: 10 Gauge Acrylic
Cuff: HPPE + Acrylic + Latex Elastic

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Product markings may vary // Updated as of 08.23



### Packaging

	Outer Polybag	Case	Made in China
GL506C	12 Pair	60 Pair	

### Glove Sizing

GL506C S – 2XL

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.