

## Neshoba™ ANSI • CE • CSA •

Frameless design with thin flexible temples // Ultra lightweight spectacle – 16 gm  
// Custom imprinting available

### Black Temples | 10 Variations

- S9710S ••• Clear
- S9710ST ••• Clear **H2X** AF
- S9710STM ••• Clear **H2MAX** AF
- S9720S ••• Gray
- S9720ST ••• Gray **H2X** AF
- S9720STM ••• Gray **H2MAX** AF
- S9730S ••• Amber
- S9760S ••• Infinity Blue
- S9770S ••• Silver Mirror
- S9780S ••• I/O Mirror



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
S9710S	P Z87 + U6	P Z87 + / P c SEI Z94.3	Weight: 16 gm	Lens: polycarbonate
S9710ST	P Z87 + U6	P Z87 + / P c SEI Z94.3	PD: 64 mm	Temples: polycarbonate
S9710STM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3	Bridge: 12.3 mm	Hinge: polycarbonate
S9720S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	Lens base: 9.5 curve	Screw: stainless steel
S9720ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	Lens size diagonal: 75.8 mm	
S9720STM	P Z87 + U6 L2.5 X	P Z87 + / P c SEI Z94.3	Lens size vertical: 43.3 mm	
S9730S	P Z87 + U6	P Z87 + / P c SEI Z94.3	Lens thickness: 1.6 mm	
S9760S	P Z87 + S	P Z87 + / P c SEI Z94.3	Overall length (lens - tip): 151 mm	
S9770S	P Z87 + S	P Z87 + / P c SEI Z94.3	Overall width (hinge - hinge): 135 mm	
S9780S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3	Closest point between temple tips: 78 mm	
			Closest point between lens: 14.5 mm	

#### Lens Marking Symbols

P: Manufacturer's mark  
Z87: ANSI standard for eye and face protection devices  
+: High impact  
X: Tested Anti-fog  
S: Special Purpose  
**UV Filter Transmittance**  
U6: .01% max effective far UV • .1% max near UV

#### Visible Light Filters

L1.7: 55% max. visible light  
L2.5: 29% max visible light

#### Temple Marking Symbols

P: Manufacturer's mark  
Z87: ANSI standard for eye and face protection devices  
+: High impact  
c SEI Z94.3: CAN/CSA standard for eye and face protection devices