



PASSIVE PRO
BASE LEVEL

PPM1 Series

PASSIVE EARMUFF



DIELECTRIC

ANSI/ASA S3.19-1974

NRR 23 dB

CAN/CSA Z94.2-2014 | CSA CLASS B

Passive Pro base level earmuff // Low profile design for maximum versatility // Soft and easy to clean ear cushions // Adjustable for custom secure fit // Comfortable vented headband // Dielectric construction is ideal for all applications, including electrical risks // Internal foam for optimal acoustics // Custom imprinting available

● PPM110 Black



Earmuff Breakdown

Headband: Acrylonitrile Butadiene Styrene
Headband Force: 2.8 lbs
Ear Cup: Polypropylene
Ear Cushion: Polyvinyl Chloride
Foam Insert: Polyurethane
Seal Plate: Polypropylene

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

Packaging

Inner Polybag: 1 unit
Case: 40 units
Made in Taiwan

NRR ATTENUATION									
FREQUENCY (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
MEANS	17.4	20.4	30.6	30.6	33.1	38.6	39.6	43.2	42.5
STANDARD DEVIATION (dB)	3.1	2.8	2.9	2.7	3.0	3.1	3.7	3.8	3.3

NRR 23dB
CSA Class B

Updated as of 03.24