



SL Series Full Brim

STANDARDS

ANSI Z89.1 • CSA Z94.1 •

High density polyethylene materials // Available with 4- and 6-point ratchet suspensions // Suspensions adjust from 6.5 - 8 head size // Passes low temperature [LT] // Meets Class E, G, and C // Hi-vis colors have been tested for the HV mark // Custom imprinting available

4-Point Ratchet | 10 Variations

- HP24110 •• White
- HP24111 •• Black
- HP24120 •• Red
- HP24130 •• Yellow
- HP24131 •• Hi-vis Lime
- HP24135 •• Green
- HP24140 •• Orange
- HP24141 •• Hi-vis Orange
- HP24160 •• Blue
- HP24162 •• Light Blue

6-Point Ratchet | 6 Variations

- HP26110 • White
- HP26120 • Red
- HP26130 • Yellow
- HP26135 • Green
- HP26140 • Orange
- HP26160 • Blue



NEED HELP
WITH YOUR
HARD HAT?



Check out these how-to guides
for accessory attachments and
suspensions



PYRAMEX

STANDARDS

ANSI Z89.1, Type 1, Class C, G, and E
CSA Z94.1

SPECS

HAT

Shell High density polyethylene

SUSPENSION

Strap Nylon

WEIGHTS AND MEASUREMENTS

Weight 394 grams / 13.9 oz

General Dimensions 6" H x 12.5" L x 10" W

Headband Sizes 6.5 - 8



FEATURES

Chin strap attachment
Replacement suspension

PRODUCT GUIDELINES

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use
Never alter or modify the shell or suspension system
Inspect the hard hat each time before use and replace if there is any sign of damage
Replace hard hat after it receives a considerable impact
Accessories such as liners have not been tested to the requirement of this standard
Clean only with mild soap and lukewarm water
Store hard hat in a clean, dry place that is out of direct sunlight
Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat
Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage